



## MISSION ADAPTIVE CHARGING STATION™ (MAX-8)

## RECHARGE MULTIPLE BATTERIES QUICKLY AND EFFICIENTLY WITH A SINGLE RUGGED SOLUTION.

**NERV CENTR MISSION ADAPTIVE CHARGING STATION** or **MAX-8** is an intelligent battery charging system that is uniquely flexible. Built to withstand the harsh conditions of expeditionary operations, the MAX-8 can draw power from virtually any source, and can charge different types of batteries simultaneously – with no reprogramming needed. The intelligent plug-and-play power management system automatically evaluates the power source and adjusts charge rates to maximize power and minimize charge time. This lightweight, rugged, charging system reduces weight and bulk, simplifies logistics, and enhances operational capability – so troops can focus on their mission, not their batteries.



The Nerv Centr® MAX-8 is smaller, lighter, and more cost-efficient than other military battery chargers – a signature design with state-of-the-art performance.

- **ADAPTABILITY** Plug-in adapter cups quickly connect different battery types in a single step without any user programming required
- **PRIORITY CHARGING** Tops off the fullest battery first, to get you back to your mission as fast as possible, with a full battery
- FAST, EFFICIENT, AND FLEXIBLE simultaneously charges different types of batteries quicker and more efficiently than other military battery chargers
- **PROVEN CAPABILITY** Used and trusted by troops around the world, including segments of the U.S. Air Force, U.S. Army, U.S. Marine Corps, international military forces, first responder teams, and commercial users
- **RUGGED DURABILITY** Impact-resistant, waterproof case ensures reliable operation in austere environments

	PART NUMBER	NATO STOCK NUMBER
MAX-8	013-453	6130-01-677-7011

## **TECHNICAL SPECIFICATIONS**

DIMENSIONS	19.78" x 15.77" x 7.41" (50.2 x 40.1 x 18.8 cm)	
WEIGHT	13.6lbs (Without AC Adapter), 17lbs (with the AC Adapter)	
BATTERY BAYS	4 Universal (accept up to 2 batteries per bay)	
USB PORTS	4 Ports compatible with iPad and other large devices	
GRAPHICAL DISPLAY	Backlit LCD Interface	
CONTROL KEYPAD	Up, Down, Enter and Escape buttons	
OPERATING TEMPERATURE	-20°C to 60°C	
STORAGE TEMPERATURE	-30°C to 70°C	
RUGGEDNESS	Meets MIL-STD-810G	
POWER INPUT	7-52V at 20A	
RATED POWER OUTPUT (WATTS)	400W	
RATED VOLTAGE AT MPP (VDC)	52V	
RATED CURRENT AT MPP (AMP)	20A	
OPEN CIRCUIT VOLTAGE	60V	
SHORT CIRCUIT CURRENT	50A	
BAY PROTECTION	Over-voltage / current, Short-circuit, Reverse Polarity, Surge	
USB OUTPUT	5A	
BATTERY COMPATIBILITY	<ul> <li>AeroVironment<sup>®</sup> RQ-11B Raven<sup>®</sup> and RQ-20 Puma<sup>®</sup></li> </ul>	
	<ul> <li>Aeryon Skyranger<sup>™</sup> R60 (platform and ground station)</li> </ul>	
	• BB-2590 / -2001 / -2557 / -2600 / -2800 / -2847	
	Conformal Wearable Battery (CWB)	
	Nerv Centr <sup>®</sup> SharePack <sup>®</sup> and SoloPack <sup>™</sup> Batteries	
	• PRC-148 / -152 / -153 / -154	

• Vector™ 120

Please contact us if you need support for a battery not listed.



The MAX-8's quick-change smart-adapter technology delivers true plug-and-play capabilities for superior ease of use and efficiency.

